

"URBAN STRUCTURE" – GENERAL CONTRACT USE SOLUTION DYED TILE



Product definition		Tufted loop pile
Gauge		1/10" Myriad
Pile fibre		100% solution-dyed polypropylene
Pile weight	ISO 8543	600 gr/m ² ± 5%
Pile height	ISO 1766	3.2mm ± 5%
Tile backing		Bitumen with glass fibre interlay
Total thickness	ISO 1765	5.6mm ± 5%
Total weight	ISO 8543	3125 gr/m ² ± 5%
Tile size		500mm × 500mm
Plank size (Special Order)		250mm × 1000mm
Tiles per box		20 (5m ²)
Use classification		Class 32 General Contract use
Castor chair test	EN 985	B, occasional use
Abrasion	EN 1963	Pass
Dimensional stability	EN 986	Pass
Sound absorption	ISO 140-8	24 dB (30 dB with Acoustic Backing)
Wear warranty		5 year general contract
Static loading		Anti-static
Reaction to fire	EN ISO 9239-1	C _{fl} -s1




30dB WHEN ORDERED WITH ACOUSTIC BACKING (24dB is standard rating)

GENERAL

Suitability	Heavy use areas: office, retail, hospitality, leisure and educational.
Recommended maintenance	Please refer to CCTUK installation and maintenance guidelines for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. For areas larger than 30m ² – it is advised that a suitable tackifier be used.
Dye lots	Colours may vary from batch to batch, it is therefore advised when ordering a large continuous area, tiles of the same batch are specified when ordering.
Pile direction	Best results are obtained when using the illustrated laying patterns.
Warranties	All warranties are subject to CCTUK T&C (available on request).



DIMENSIONS



TILES: 500 × 500mm
PLANKS: 250 × 1000mm
 (available by Special Order only)

For a brochure, photos and more information, please visit www.urbanstructurecarpettiles.co.uk

commercialcarpettilesuk.co.uk

Tel: 01793 317940 Email: sales@cctuk.ltd

Unit 5 Pagoda Park, Westmead Industrial Estate, Swindon, SN5 7UN

